

ATM-LEVAGE

Location de grues, mini-grues & nacelles

ELAN MP

The multi-purpose car mover



ZERO EMISSION


HANDLING CRANE

8.5 TO
15 TXM



TOWING FORCE

<80 TONS



DIESELSTAGE V 45 KW

Green-e 30 KW



13, M

<6, 15 M

OPTIONAL

OHL AERIAL PLATFORM

230 KG

ATM-LEVAGE

Location de grues, mini-grues & nacelles

ELAN MP

TECHNICAL DATA



Green-e POWER PACK OPTION

Electric motor max power 30 kW
Battery LFP 48V/200Amp/h .. ZERO emission range >10 km*
Max speed - Electric mode 20 kph
Battery recharge by diesel 50% / 45 min
Plug-in 110/220V-16A

*Following standard working cycle

GENERAL DATA

PERKINS HVO Diesel engine - STAGE V 45 kW
Dimensions 5 371 x 2 530 mm
Weight in operation up to 13 000 kg

OFF-ROAD MODE

Rubber track x 2 2 500 x 400 mm
Hydrostatic drive 1 motoreducer/track
Off-road speed From 0 to 1,5 kph
Gradient capability Up to 45% on stable ground

RAIL MODE

Driven and braked axles x 2 NEOTEC EPV 06.32
Oscillating axle with hydraulic locks x 1
Brakes (disc/axle) Hydrostatic/Service/Park
Diameter of railway wheels Ø 580 mm
Max gradient 1/25 - 40‰/60‰ (option)
Max cant 200 mm
Inspection speed 5 kph
Max travelling speed 20 kph

OPTION

220/110V-3.5kVA Genset
Handing cranes: 7/12.5/15 t/m
Large cab (5 persons)
Vertical access basket (230 kg/2persons)

